

AT-C4G08



- 8 Channels DVR
- FULL D1 Realtime
- 960H 100FPS
- HDMI Output
- IR Extension Cable

Video Compression	H.264	
Video System	NTSC/PAL	
Operation System	Linux(embedded)	
Video-input /output	8CH input /1CH output(BNC)	
Audio input /output	8CH input /1CH output(RCA)	
Display	resolution	PAL:960×576@25fps(each channel) NTSC:960×480@30fps(each channel)
	feature	single/ Quad/Nine/S.E.Q.
Record	resolution	PAL : D1 mode : 360x288(CIF),720x288(HD1),720x576(D1) 960H mode :480x288(WCIF),960x288(WHD1),960x576(WD1) NTSC: D1 mode :360x240(CIF),720x240(HD1),720x480(D1) 960H mode :480x240(WCIF),960x240(WHD1),960x480(WD1)
	speed	PAL: (each ch,Frame) CIF/HD1/D1:25fps, WCIF:25fps; WHD1/ WD1:9fps NTSC: (each ch,Frame) CIF/HD1/D1:30fps, WCIF:30fps; WHD1/ WD1:11fps
Recording Mode	Continuous/Manual/Motion detected/Alarm Activated	
Playback Channel	1/4/9ch	
Playback speed (simultaneously Record)	8CH	PAL: (each channel) CIF /HD1/D1 :25fps, WCIF:25fps, WHD1/ WD1:19fps 8CH Playback: 12fps@D1&HD1&CIF, 25fps@WCIF,9fps@WD1&WHD1 NTSC:(each channel) 1~4CH Playback: CIF /HD1/D1 :30fps, WCIF:30fps, WHD1/ WD1:23fps 8CH Playback: 15fps@D1&HD1&CIF, 30fps@WCIF,11fps@WD1&WHD1
Sensor & Alarm I/O	8ch sensor input&1 channel alarm out	
IR Extender Port	Yes	
Network	Lan, DHCP, Dynamic IP and DDNS	
HDD interface	1SATA HDDs, up to 4TB	
Multiplex Operation	live display, record, playback, backup and network	
USB	2xUSB(for mouse and backup/upgrade)	
PTZ Control	Built in RS485, support Pelco-P & Pelco-D	
Mobile Surveillance	Support Mobile Phones based on iPhone and Android operation system	
VGA	800*600,1024*768, 1280*1024,1440*900, 1920*1080	
HDMI	1080P	
Power Supply	DC 12V 2A	
Dimension(wxDxH)	300X227X53mm	